

Empty enclosure

TK PC 1313-10-tm



TK PC 1313-10-tm

Empty enclosure

CUSTOMIZABLE

Productnumber: 13750501
Dimensions: 130 x 130 x 99 mm

Empty enclosure - Industrial Quality -, Base and cover: glass fibre reinforced polycarbonate, Grey, similar to RAL 7035

with metric knockouts



Technical Data

electrical characteristics

Protection type UL:	4X
Type of protection:	IP66
Protection class:	II
Rated insulation voltage AC:	690 V
Rated insulation voltage DC:	1000 V

Colours

Base unit colour:	grey
Cover colour:	transparent

Dimensions

Length:	130 mm
---------	--------

Dimensions

Width:	130 mm
Height:	99 mm

Material characteristics

suitable for exterior use:	yes
Halogen free:	yes
Industry quality:	yes

mechanical properties

Type of fastening:	yes
Sealable:	yes
Cover screw torque:	1.2 Nm
Stackable:	yes
Impact strength:	IK08

Ambient conditions

max. relative humidity 25°C:	95 %
24h ambient temperature:	60
Min. ambient temperature:	-35
Max. ambient temperature:	80
max. relative humidity 40°C:	50 %

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Certificates

Test mark:	DLG
Test mark:	c UL us
Test mark:	DNVGL

Accessories

HBA - Mounting material

ASS-kl - External hinge set

TK ABL - External fixing lugs kit

TK DST - Spacing kit

TK MPI-1313 - Mounting plate

TS 15-111 - Standard rail

NS 35-81 - Standard rail

NS 35-106 - Standard rail