

Empty enclosure

TK PS 3625-16-m



TK PS 3625-16-m

Empty enclosure

CUSTOMIZABLE

Productnumber: 10591201

Dimensions: 361 x 254 x 165 mm

Empty enclosure IP66 polystyrene

Box and cover, polystyrene, grey similar to RAL 7035, metric pre-embossings

IP66

IK07



690V
AC

1000V
DC



To industrial product:

<https://www.spelsberg.com/p/12791201>

Technical Data

electrical characteristics

Protection type UL:	not specified
Rated insulation voltage AC:	690 V
Rated insulation voltage DC:	1000 V
Type of protection:	IP66
Protection class:	II

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Length:	254 mm
Width:	361 mm

Dimensions

Height:	165 mm
---------	--------

Material characteristics

suitable for exterior use:	no
Halogen free:	yes
Industry quality:	no

mechanical properties

Type of fastening:	Wall/ceiling mounting
Sealable:	yes
Cover screw torque:	1.2 Nm
Stackable:	yes
Impact strength:	IK07

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25
Max. ambient temperature:	40
24h ambient temperature:	35

Material

Base unit material:	Polystyrene
Cover material:	Polystyrene
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

HBA - Mounting material

ASS-gro - External hinge set

TK ABL - External fixing lugs kit

TK MPI-3625 - Mounting plate

NS 35-216 - Standard rail

NS 35-336 - Standard rail