

Empty enclosure

TK PC 2518-6f-tm



TK PC 2518-6f-tm

Empty enclosure

CUSTOMIZABLE

Productnumber: 13701101
Dimensions: 254 x 180 x 63 mm

Empty enclosure IP66 polycarbonate

Box, glass fibre reinforced polycarbonate, grey similar to RAL 7035, transparent polycarbonate cover, metric pre-embossings



Technical Data

electrical characteristics

| | |
|------------------------------|--------|
| Protection type UL: | 4X |
| Rated insulation voltage AC: | 690 V |
| Rated insulation voltage DC: | 1000 V |
| Type of protection: | IP66 |
| Protection class: | II |

Colours

| | |
|-------------------|-------------|
| Base unit colour: | grey |
| Cover colour: | transparent |

Dimensions

| | |
|---------|--------|
| Length: | 180 mm |
| Width: | 254 mm |

Dimensions

| | |
|---------|-------|
| Height: | 63 mm |
|---------|-------|

Material characteristics

| | |
|----------------------------|-----|
| suitable for exterior use: | yes |
| Halogen free: | yes |
| Industry quality: | yes |

mechanical properties

| | |
|---------------------|-----------------------|
| Type of fastening: | Wall/ceiling mounting |
| Sealable: | yes |
| Cover screw torque: | 1.2 Nm |
| Stackable: | yes |
| Impact strength: | IK08 |

Ambient conditions

| | |
|------------------------------|------|
| max. relative humidity 25°C: | 95 % |
| max. relative humidity 40°C: | 50 % |
| Min. ambient temperature: | -35 |
| Max. ambient temperature: | 80 |
| 24h ambient temperature: | 60 |

Material

| | |
|-----------------------|-----------------------------------|
| Base unit material: | Polycarbonate |
| Cover material: | Polycarbonate |
| Sealing material: | Polyurethane |
| Cover screw material: | Polyamide, glass-fibre reinforced |

Certificates

| | |
|------------|---------|
| Test mark: | c UL us |
| Test mark: | DLG |
| Test mark: | DNVGL |

Accessories

HBA - Mounting material

ASS-gro - External hinge set

TK ABL - External fixing lugs kit

TK MPI-2518 - Mounting plate

NS 35-216 - Standard rail