

Empty enclosure

TK PS 2518-6f-to



TK PS 2518-6f-to

Empty enclosure

CUSTOMIZABLE

Productnumber: 11101101
Dimensions: 254 x 180 x 63 mm

Empty enclosure IP66 polysterene

Box, polystyrene, grey similar to RAL 7035, transparent polycarbonate cover, without pre-embossings



To industrial product:
<https://www.spelsberg.com/p/13001101>

Technical Data

electrical characteristics

Protection type UL:	not specified
Rated insulation voltage AC:	690 V
Rated insulation voltage DC:	1000 V
Type of protection:	IP66
Protection class:	II

Colours

Base unit colour:	grey
Cover colour:	transparent

Dimensions

Length:	180 mm
---------	--------

Dimensions

Width:	254 mm
Height:	63 mm

Material characteristics

suitable for exterior use:	no
Halogen free:	yes
Industry quality:	no

mechanical properties

Type of fastening:	Wall/ceiling mounting
Sealable:	yes
Cover screw torque:	1.2 Nm
Stackable:	yes
Impact strength:	IK07

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25
Max. ambient temperature:	40
24h ambient temperature:	35

Material

Base unit material:	Polystyrene
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

HBA - Mounting material

ASS-gro - External hinge set

TK ABL - External fixing lugs kit

TK MPI-2518 - Mounting plate

NS 35-216 - Standard rail