

Empty enclosure

# TK PC 1309-8-tm



## TK PC 1309-8-tm

Empty enclosure

CUSTOMIZABLE

Productnumber: 13750901

Dimensions: 94 x 130 x 81 mm

Empty enclosure - Industrial Quality -, Base and cover: glass fibre reinforced polycarbonate, Grey, similar to RAL 7035

with metric knockouts



## Technical Data

### electrical characteristics

|                              |        |
|------------------------------|--------|
| Protection type UL:          | 4X     |
| Type of protection:          | IP66   |
| Protection class:            | II     |
| Rated insulation voltage AC: | 690 V  |
| Rated insulation voltage DC: | 1000 V |

### Colours

|                   |             |
|-------------------|-------------|
| Base unit colour: | grey        |
| Cover colour:     | transparent |

### Dimensions

|         |       |
|---------|-------|
| Length: | 94 mm |
|---------|-------|

## Dimensions

|         |        |
|---------|--------|
| Width:  | 130 mm |
| Height: | 81 mm  |

## Material characteristics

|                            |     |
|----------------------------|-----|
| suitable for exterior use: | yes |
| Halogen free:              | yes |
| Industry quality:          | yes |

## mechanical properties

|                     |        |
|---------------------|--------|
| Type of fastening:  | yes    |
| Sealable:           | yes    |
| Cover screw torque: | 1.2 Nm |
| Stackable:          | yes    |
| Impact strength:    | IK08   |

## Ambient conditions

|                              |      |
|------------------------------|------|
| max. relative humidity 25°C: | 95 % |
| 24h ambient temperature:     | 60   |
| Min. ambient temperature:    | -35  |
| Max. ambient temperature:    | 80   |
| max. relative humidity 40°C: | 50 % |

## Material

|                       |                                   |
|-----------------------|-----------------------------------|
| Base unit material:   | Polycarbonate                     |
| Cover material:       | Polycarbonate                     |
| Sealing material:     | Polyurethane                      |
| Cover screw material: | Polyamide, glass-fibre reinforced |

## Certificates

|            |         |
|------------|---------|
| Test mark: | DLG     |
| Test mark: | c UL us |
| Test mark: | DNVGL   |

## Accessories

HBA - Mounting material

ASS-kl - External hinge set

TK ABL - External fixing lugs kit

TK DST - Spacing kit

TK MPI-1309 - Mounting plate

TK TW-n - Partition wall

TK TW-h - Partition wall

TS 15-111 - Standard rail

NS 35-81 - Standard rail

NS 35-106 - Standard rail