

Empty enclosure

## AKL 2-gh



### AKL 2-gh

Empty enclosure

CUSTOMIZABLE

Productnumber: 74290201

Dimensions: 300 x 300 x 209 mm

Empty enclosure IP65 polysterene

**Box and cover, polystyrene, grey similar to RAL 7035, metric pre-embossings**



To industrial product:

<https://www.spelsberg.com/p/74390201>

## Technical Data

### electrical characteristics

Protection type UL:	not specified
Rated insulation voltage AC:	690 V
Rated insulation voltage DC:	1000 V
Type of protection:	IP65
Protection class:	II

### Colours

Cover colour:	grey
---------------	------

### Dimensions

Length:	300 mm
Width:	300 mm
Height:	209 mm

## Material characteristics

suitable for exterior use:	yes
Burning behaviour in accordance with UL 50/UL 746C:	HB
Burning behaviour in accordance with UL 94:	V2
Burning behaviour in accordance with VDE:	750
Halogen free:	yes
Industry quality:	no

## mechanical properties

Type of fastening:	Wall/ceiling mounting
Sealable:	yes
Stackable:	yes
Impact strength:	IK07

## Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25
Max. ambient temperature:	40
24h ambient temperature:	35

## Material

Base unit material:	Polystyrene
Cover material:	Polystyrene
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

## Accessories

ASS-gro - External hinge set

AK NS35-250 - Standard rail

AK ABL-ES - External fixing lugs

AK MPI 2 - Mounting plate

NS35-216/3 - Standard rail

AK ABF 2 - Enclosure wall smooth

AK TW - Partition wall