

Junction box

HP 150-L



HP 150-L

Junction box

Productnumber: 32695001

Dimensions: 119 x 164 x 77 mm

Junction box, $U_i=690V$, 10 recessed stepped nipples, seal range 5 - 21 mm

Grey, without terminals, with cover retainer



Technical Data

electrical characteristics

Protection type UL:	not specified
Type of protection:	IP55
Circuit integrity class:	none
Max. conductor cross section:	10
Protection class:	II
Rated insulation voltage AC:	690 V

Dimensions

Length:	119 mm
Width:	164 mm
Height:	77 mm
Inner length:	110 mm

Dimensions

Inner width:	155 mm
Inner height:	70 mm

Material characteristics

suitable for exterior use:	no
Halogen free:	no
Industry quality:	no

mechanical properties

Type of fastening:	Wall/ceiling mounting
Sealable:	no
Impact strength:	IK07

Ambient conditions

max. relative humidity 25°C:	95 %
24h ambient temperature:	35
Min. ambient temperature:	-25
Max. ambient temperature:	40
max. relative humidity 40°C:	50 %

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

Certificates

Test mark:	VDE
------------	-----

Accessories

NS 35-106 - Standard rail
NS 35-144 - Standard rail
SNI M25 - Stepped nipple
KVR M25-MGM - Cable gland
WK 100 KLS-10 ² - Terminal block
NS 35-90 - Standard rail