

2570.0

Q 10

Q 10



Cross-connector, No. of poles: 10, Mounting type: Can be screwed on, Width: 49.9 mm, Rated cross-section: 2.5 mm², Colour: natural

Business data

| | |
|--|-----------------|
| Product description | Cross-connector |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 11 |
| Weight per piece (including packaging) | 11.1 |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |

2570.0

Q 10

Q 10

Technical Data

Dimensions

| | |
|---------------------------------------|---------|
| Length | 4 mm |
| Width | 49.9 mm |
| Hole height | 2.5 mm |
| Hole diameter | 2.8 mm |
| Hole spacing (mid-point to mid-point) | 5.1 mm |
| Pitch size | 5 mm |
| Slotted hole | ✓ |

Ratings

| | |
|---------------------------------|---------------------|
| Voltage with partition, max. | 800 V |
| Voltage without partition, max. | 400 V |
| Rated current | 20 A |
| Rated cross-section | 2.5 mm ² |
| Contamination degree | 3 |

2570.0

Q 10

Q 10

Technical Data

Connection data

| | |
|-------------------------|---------|
| No. of poles | 10 |
| Screw head | Slotted |
| Screw threading | M 2,5 |
| Tightening torque, min. | 0.4 Nm |
| Tightening torque, max. | 0.8 Nm |

Materials

| | |
|---------------|------------|
| Material | Copper |
| Surface | Tin-plated |
| Surface screw | Galvanized |

Further technical data

| | |
|-----------------------------|-----------|
| Mounting type | Screwable |
| Number of bridged terminals | 10 |

2570.0

Q 10

Q 10

Media

M2.5



2570.0

Q 10

Q 10

Accessories

Screw driver



Screwdriver with bare blade, Colour: Black-grey

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 1086.0 | SDB 0,6x3,5 | 4044211014797 | 1 PC |
